

The DPX[®]-E105 is a complete industrial computer system that offers good performance and very low power with the cost effective Intel[®] ATOM[™] processor. A full feature set of I/O and COMs designed specifically for gaming devices is also included making the DPX[®]-E105 an ideal integrated platform for many gaming, amusement and kiosk applications. The overall system is fanless and the gaming functions share the same API as Innocore's other DPX[®]- series boards.

FEATURE SUMMARY

System:

- Intel[®] ATOM[™] performance & low power
- Intel 945GSE chipset
- 512MB DDR2 SDRAM
- 1 x Gb Ethernet LAN
- 2 x Compact Flash socket
- Audio
- 1024kB SRAM

I/O:

- 5 x RS232 Serial, 16550 compatible (2 x available as TTL)
- 1 x CCTalk
- 5 x USB 2.0
- 32 inputs and 32 outputs

Video:

- Integrated Intel GMA 950 (Gen. 3.5)
- Dual monitor support

Security:

- Intrusion switch inputs
- BIOS customization
- 1 x iButton[®] sockets
- 1 x Security ROM socket

Enclosure:

- Aluminium extruded with status LEDs.
- Passive cooling system

Software:

- Edge-to-edge drivers and API/SDK.
- Code portability through consistent API with other Innocore boards.
- Range of Innocore software products for Gaming



Front I/O



Rear I/O

BENEFITS

- Low Power (CPU power 2.5W, overall power TBC)
- Single integrated solution
- Small size - 229x180x77mm (9.0x7.1x3.0")
- Designed for the Gaming Industry
- Low Cost



See overleaf detailed specification

CPU/Chipset:

Intel[®] ATOM[™] N270 1.6GHz (1.6/533 2.5W)

Intel[®] 945GSE + ICH7M

Memory:

1 x SODIMM socket
512MB DDR2 533MHz

Optional* :-
Up to 2GB

BIOS:

AMI PCI/PnP/ACPI BIOS

Video:

Integrated - Intel GMA 950

Video Ports:

Primary:- Analog VGA
Secondary:- DVI

LAN:

1 x Ethernet Gigabit LAN
Full duplex operation
Wake-On-LAN capability

Storage:

2 x CompactFlash Type I/II
(Flash/MicroDrive)**

Optional* :-
1 x CF socket configured for SD card**
1 x HDD/SSD 2.5***

Ports:

5 x RS232 Serial, 16550 compatible (2 x available as TTL)

1 x CCTalk
4 x USB 2.0
1 x USB 2.0**

Optional* :-
1 x CCTalk
2 x RS232
1 x RS485

I/O:

32 ESD protected inputs
32 OC Outputs (250mA, 50V)

Optional* :-
4 Opto-Isolated outputs
4 high current outputs (3A)

Power Fail Detect

External sensor input for advanced warning of AC power fail

Sound:

HD Audio
2 channel line level outputs

SRAM:

1024kB fast SRAM (1 bank) on PCI bus
Battery state software readable

Optional* :-
Up to 4096kB

EEPROM:

Optional* :-
32kB user EEPROM

iButton

1 x iButton[®] socket for special purpose device or security modules**

Optional* :-
1 x iButton[®]**

Security ROM:

1 x Socket for 1MB EPROM/OTPROM
PLCC32 (PCI, Bootable)

Optional* :-
1 x Socket for 1MB EPROM/OTPROM
PLCC32 (PCI, Bootable)

Watchdog Timer:

Programmable time-out of 1-255 seconds
"Always on" design (default 255 seconds)

Intrusion Detection:

Six Intrusion detection input lines (2 used for 'case open')
Operates with and without system active
Logs date/time of last 254 events
Logs system resets/brownouts as events
EEPROM backup for 10 years retention

System Health Monitoring:

Measurement of CPU core temp. With thermal trip.

Power:

ATX or AT mode
External PSU.

Environment:

Operating Temperature: 0 – 40 °C TBC
Storage Temperature: -20 – 85 °C

Approvals:

EMC: CE, FCC Class A
RoHS, WEEE

Dimensions:

229x180x77mm (9.0x7.1x3.0")

Optional Hardware:

- Edge card connector set
- Compact Flash cards
- USB sticks
- External power supply
- iButtons[®]

**OEM Customization and Product Development:**

Innocore specializes in the fields of PC-based hardware design and software development. Our in-depth knowledge and global resources make us your ideal partner.

Specifications subject to change. E&OE.
Copyright © 2009 Innocore Gaming Ltd.
All rights reserved. Innocore, the Innocore Logo, DPX, ConnectBus are trademarks of Innocore Gaming Ltd in the UK, US and other countries. All other trademarks are acknowledged and respected

Notes:-

* - Optional items are subject to an MOQ, price change and are factory configured at time of order.

** - User Accessible (Internally mounted behind rear cover plate under battery backed intrusion detection)